

(12) **UK Patent Application** (19) **GB** (11) **2 374 790** (13) **A**

(43) Date of A Publication 30.10.2002

(21) Application No 0109973.8

(22) Date of Filing 23.04.2001

(71) Applicant(s)

General Mills Inc
(Incorporated in USA - Delaware)
Number One General Mills Boulevard, Minneapolis,
Minnesota 55426, United States of America

(72) Inventor(s)

Gary S Bachand
Soumya Roy
Jeffrey A Taylor
Craig E Zimmermann

(74) Agent and/or Address for Service

Frank B Dehn & Co.
179 Queen Victoria Street, LONDON, EC4V 4EL,
United Kingdom

(51) INT CL⁷

A23G 3/00

(52) UK CL (Edition T)

A2B BMC2

(56) Documents Cited

US 5853836 A

US 5455053 A

US 3798343 A

US 3704664 A

(58) Field of Search

UK CL (Edition S) **A2B BMB11 BMB19 BMB21 BMC12**
BMC17 BMC2 BMC7 BMP1 BMP5

INT CL⁷ **A21C 9/06 , A21D 13/00 13/08 , A23G 3/00**
3/02 , A23L 1/212 , A23P 1/08

Online: **EPODOC, WPI, JAPIO**

(54) Abstract Title

Rolled food item

(57) A method for making a rolled food item 110 comprises the steps of providing a strip of support material 16 and food 14, spraying moisture at least on the edge of food that will constitute the centre of the roll 136, and then rolling the strip into a roll with the support material on the outside of the roll. The food may be a sweetened dehydrated fruit based material, and the support material is preferably silicon parchment paper. The moisture sprayed onto the food is preferably food grade water free of adhesive type additives.




FIG. 2

GB 2 374 790 A

1/2




FIG. 1




FIG. 2

2/2




FIG. 3a




FIG. 3b

1 Labelless, Rolled Food Item And Its Fabrication

The present invention generally relates to food items, particularly to rolled food items, more particularly to coils of food supported on support material, and specifically to rolled food items or the like at least temporarily retained in a coiled condition without the use of a label during its fabrication.

The sale of snack-type food products is a highly competitive business. In addition to the particular food components, increasingly the novelty and play value of the product are important in the marketability of any particular food item. For example, fruit-based snack products such as FRUIT ROLL-UPS™ fruit products have found wide market acceptance. Likewise, U.S. Patent No. 4,882,175 recognized the enhanced marketability of chewing gum in the form of a rolled-up tape allowing the consumer the chance to break off the desired size of piece to chew, saving the rest for later.

20 Many foods such as dehydrated fruit puree do not lend themselves to forming rolled food items such as where the food is in a strip of a thinness generally requiring external support and/or where the food tends to stick to itself such that it creates a single mass which can not be unrolled. In such cases, support material and food supported thereon are rolled into a coil creating a novelty form of merchandising for that food. For example, FRUIT BY THE FOOT™ fruit products of the type disclosed in U.S. Patent Nos. 5,455,053 and 5,723,163 have enhanced play value which is believed to promote the marketability thereof.

During the fabrication of rolled food items, provisions have to be made to prevent the food item from unrolling during fabrication such as in the wrapping and other packaging operations. A prior preferred method to prevent undesired unrolling is the application of a label extending over the trailing edge of the support material.

1 In addition to its functional aspects, the labels used to
hold the rolled food items in a coiled condition can add
to the novelty and play value of the rolled food item.
Particularly, the label often includes graphics which are
5 visually appealing to the typical consumer of the food of
the rolled food item and/or which promote the future
purchase of the rolled food item. However, problems arose
from the labels which had not been appropriately discarded
after their removal from the rolled food item being
10 difficult to remove when adhered to surfaces such as desk
tops. One solution to this problem was to provide novel
labels for such rolled food items such as of the type
disclosed in U.S. Patent Appln. No. 08/888,803 filed July
7, 1997, which is hereby incorporated herein by reference.

15 Another prior method to prevent unintentional
unrolling is to utilize an edible adhesive such as corn
syrup. However, corn syrup and similar adhesives have
certain negatives including being an additive to the food
which could affect its taste, texture, and/or appearance,
20 being messy while eating and also during application and
fabrication and being generally difficult to work with.

Accordingly, it is an object of the present invention
to provide novel apparatus and methods for fabrication of
a novel rolled food item which, in the preferred form, is
25 retained at least temporarily in a coiled condition during
fabrication such as in the wrapping and other packaging
operations without the use of a label and which overcomes
the negatives associated with the use of corn syrup and
similar food adhesives.

30 Another object of the present invention is to allow
the retention of the rolled food item in a coiled
condition without the use of a label and without
significant change to existing fabrication equipment and
its operating conditions.

35

Surprisingly, the above objectives and other problems
can be satisfied in the field of rolled food items and

their fabrication by providing, at least in the preferred form, a first portion of the food adjacent the trailing edge having a moisture content greater than the remaining portions of the food and sufficient to
5 increase the tackiness of the food to be adherable to the support material to retain the support material and food in a roll and to at least temporarily prevent unintentional unrolling of the roll during fabrication of the rolled food item.

10 Viewed from one aspect the present invention provides a rolled food item comprising, in combination: a strip of support material and food, with the strip of support material and food having a trailing edge and a leading edge, with the strip of support material and
15 food being rolled in a roll having a periphery and a center, with the support material located on the outside of the roll, with the trailing edge located on the periphery of the roll, with the leading edge located adjacent the center of the roll, with the food having a first portion adjacent the trailing edge and a second portion of a substantially longer length than the first portion, with the first portion of the food having a
20 moisture content greater than the moisture content of the second portion and so that the tackiness of the food is sufficient to adhere to the support material in the roll to at least temporarily prevent unintentional
25 unrolling of the roll.

At least in the preferred form, the first portion of the food is formed by spraying a source of moisture, and in the most preferred form a food grade water free
30 of adhesive type additives, onto the food adjacent to the trailing edge prior to its rolling into the roll.

Viewed from another aspect the present invention provides a method for fabricating a rolled food item, comprising the steps of: providing a strip of support
35 material and food, with the strip of support material and food having a trailing edge and a leading edge, with

the food having a tackiness; rolling the strip of support material and food into a roll having a periphery and a center, with the support material located on the outside of the roll, with the trailing edge located on the periphery of the roll and with the leading edge located adjacent the center of the roll; and spraying a deposit of a source of moisture at least on the food adjacent to the trailing edge prior to its rolling into the roll, with the source of moisture increasing the tackiness of the food sufficient to be adherable to the support material in the roll to at least temporarily prevent unintentional unrolling of the roll.

Viewed from another aspect the present invention provides an apparatus for fabricating a rolled food item, comprising, in combination: means for providing a strip of support material and food, with the strip of support material and food having a trailing edge and a leading edge, with the food having a tackiness; means for rolling the strip of support material and food into a roll having a periphery and a center, with the support material located on the outside of the roll, with the trailing edge located on the periphery of the roll and with the leading edge located adjacent the center of the roll; means for spraying a deposit of a source of moisture at least on the food adjacent to the trailing edge prior to its rolling into the roll, with the source of moisture increasing the tackiness of the food sufficient to be adherable to the support material in the roll to at least temporarily prevent unintentional unrolling of the roll.

The present invention will become clearer in light of the following detailed description of an illustrative embodiment of this invention described in connection with the drawings.

The illustrative embodiment may best be described by reference to the accompanying drawings where:

Figure 1 shows a top plan view of a strip of

support material and food according to the preferred teachings of the present invention, with portions broken away.

5 Figure 2 shows a side elevational view of the strip of support material and food of Figure 1 rolled into a roll to form a rolled food item.

10 Figures 3a and 3b show diagrammatic side elevational views of the apparatus for rolling the strip of support material and food of Figure 1 to form the rolled food item of Figure 2.

15 All figures are drawn for ease of explanation of the basic teachings of the present invention only; the extensions of the figures with respect to number, position, relationship, and dimensions of the parts to

1 form the preferred embodiment will be explained or will
be within the skill of the art after the following
description has been read and understood. Further, the
exact dimensions and dimensional proportions to conform
5 to specific force, weight, strength, and similar
requirements will likewise be within the skill of the
art after the following description has been read and
understood.

Where used in the various figures of the drawings,
10 the same numerals designate the same or similar parts.
Furthermore, when the terms "first", "second", "edge",
"end", "transverse", "longitudinal", "width", "length",
"height", "inner", "outer", "leading", "trailing", and
similar terms are used herein, it should be understood
15 that these terms have reference only to the structure
shown in the drawings as it would appear to a person
viewing the drawings and are utilized only to facilitate
describing the illustrative embodiment.

20 A rolled food item according to the preferred
teachings of the present invention is shown in the
drawings and generally designated 110. In the most
preferred embodiment of the present invention, rolled
food item 110 is an improvement of the type shown and
25 described in U.S. Patent Nos. 5,205,106; 5,284,667;
5,455,053 and 5,723,163. For purpose of explanation of
the basic teachings of the present invention, the same
numerals designate the same or similar parts in the
present figures and the figures of U.S. Patent Nos.
30 5,205,106; 5,284,667; 5,455,053 and 5,723,163. The
description of the common numerals and rolled food item
110 may be found herein and in U.S. Patent Nos. 5,205,106;
5,284,667; 5,455,053 and 5,723,163, which are hereby
incorporated herein by reference.

35 Generally, rolled food item 110 includes strips of

1 food 14 and support material 16 simultaneously rolled
about its leading edge or end 136 into a coil. Food 14 is
of a thinness requiring external support by support
material 16. In the most preferred form, food 14 is a
5 sweetened dehydrated fruit-based material typically
referred to in the art as a fruit leather which can be
derived from fruit purees and in the most preferred form
is of the same type as utilized in the first, solid or
"hard" portion or region of the dual textured food piece
10 described in U.S. Patent No. 4,847,098 issued July 11,
1989 to J.E. Langler and in U.S. Patent No. 4,853,236
issued August 1, 1989 to J.E. Langler, each entitled Dual
Textured Food Piece of Enhanced Stability and each of
which is hereby incorporated herein by reference.

15 Support material 16 may be formed of any suitable
material such as silicon parchment paper which has the
necessary strength to support food 14 without tearing and
without bulkiness to allow rolling of food 14 and support
material 16 into a compact food piece and which allows
20 food 14 to be easily separated therefrom for consumption.

In the preferred form, the strip of food 14 has side
edges spaced inwardly from the side edges of the strip of
support material 16 and in the most preferred form are
spaced in the order of one sixteenth inch (1.6 mm)
25 inwardly from the side edges of the strip of support
material 16. Depending upon the method of fabrication,
spacing the strip of food 14 inward of the side edges of
the strip of support material 16 is advantageous as food
14 has less tendency to rub against the fabrication
30 equipment which is undesirable as the side edges of the
strip of food 14 could acquire an unsightly or otherwise
undesirable appearance and as food 14 could build up or
otherwise collect on the fabrication equipment requiring
extra cleaning and maintenance. In the preferred form,
35 the strip of food 14 does not extend beyond the leading
end 136 and trailing edges or ends 138 of the strip of

1 support material 16 and in the most preferred form has a
length equal to the length of the strip of support
material 16 so that leading and trailing ends 136 and 138
of the strip of food 14 are coextensive with leading and
5 trailing ends 136 and 138 of the strip of support material
16. Specifically, in the most preferred form, the strips
of food 14 and support material 16 are formed continuously
and are simultaneously cut to length such as by a water
knife. In the preferred form, the width of the strip of
10 support material 16 is minimal relative to its length and
in the most preferred form, the strip of support material
16 has a width in the order of one and one-eighth inch
(2.9 cm) and a length in the order of 36 inches (1 meter).

The strips of food 14 and support material 16 are
15 rolled around their leading edges or ends 136 into the
coil having multiple rotations with the strip of support
material 16 located on the outside of the roll or coil and
with trailing edge 138 of the strips of food 14 and
support material 16 located on the outside or periphery of
20 the roll or coil. In the most preferred form, when the
strips of food 14 and support material 16 are rolled, the
periphery of the coil or roll is in the order of four and
five-eighths inches (11.7 cm).

In the production of rolled food item 110, generally
25 one or more strips of food 14 and support material 16 are
transported in a generally planar condition such as on a
conveyor 140 towards a roll-up section 76. It can be
appreciated that strips of food 14 and support material 16
can be formed in a variety of manners according to the
30 teachings of the present invention including but not
limited to the type disclosed in U.S. Patent Nos.
5,205,106; 5,284,667; 5,455,053 and 5,723,163. Similarly,
roll-up section 76 can be of a variety of forms according
to the teachings of the present invention including but
35 not limited to the type utilizing a reciprocable,
rotatable tuning fork disclosed in U.S. Patent Nos.

1 5,205,106; 5,284,667; 5,455,053 and 5,723,163.

According to the teachings of the present invention, rather than providing a labeler and a label smasher as in U.S. Patent Nos. 5,205,106; 5,284,667; 5,455,053 and
5 5,723,163, one or more spray nozzles 142 are provided vertically above and spaced from conveyor 140 and spaced in a manner to not physically contact the strips of food 14 and support material 16 on conveyor 140 and upstream of roll-up section 76. According to the teachings of the
10 present invention, nozzles 142 spray a source of moisture in the preferred form of a liquid consisting of food grade water. In the preferred form, the water is free of adhesive type additives such as corn syrup and in the most preferred form is free of all additives.

15 In a preferred form, a fewer number of nozzles 142 are provided than the number of strips of food 14 and support material 16, with each nozzle 142 spraying a source of moisture over more than one strip of food 14 and support material 16. In this regard, four nozzles 142 could be
20 provided to spray ten strips of food 14 and support material 16. In other forms, a separate nozzle 142 can be associated and transversely aligned with each strip of food 14 and support material 16. In such preferred forms, each nozzle 142 can have a spray pattern having a
25 transverse width less than the width of the strip of support material 16, preferably less than the width of the strip of food 14, and most preferably approximately two thirds the width of the strip of food 14.

According to the teachings of the present invention,
30 operation of each nozzle 142 is not continuous, but rather nozzles 142 spray a deposit 144 adjacent to trailing end 138 of the strips of food 14 and support material 16 and in the most preferred form with deposit 144 having a trailing end coextensive with the trailing end 138 of the
35 strips of food 14 and support material 16, with deposit 144 extending upstream from trailing end 138. Deposit 144 which defines a first portion has a relatively short

1 length considerably shorter than the remaining, second
portion of the strips of food 14 and support material 16
and than the total elongated length of the strips of food
14 and support material 16, with deposit 144 in the most
5 preferred form being generally 10% of the elongated length
of the strips of food 14 and support material 16. In the
preferred form shown, deposit 144 has side edges spaced
inwardly from and parallel to the side edges of food 14.
According to the teachings of the present invention, the
10 remaining second portions of the strips of food 14 and
support material 16 (other than deposit 144) are free of
spray liquid. In this regard and in the most preferred
form, air is blown through nozzles 142 after supply of the
spray liquid has been terminated to nozzles 142 to remove
15 any droplets of spray liquid that have remained in the tip
of nozzles 142 to insure that such droplets fall in deposit
144 and not after leading edge 136 of the next strip of food
14 and support material 16.

Food 14 as processed during fabrication has a moisture
20 content which enhances its shelf life, and particularly has
a moisture content which does not result in food 14
undesirably degrading during normal storage times before
consumption. With this moisture content, food 14 has a
tackiness which may adhere to support material 16 when
25 rolled into a roll but typically which is insufficient to
prevent unintentional unrolling during further fabrication
processes such as wrapping and other packaging operations.
However, food 14 within deposit 144 has an increased
moisture content so that food 14 becomes sticky or in
30 other words has an increased tackiness sufficient to
adhere to support material 16 in the roll to prevent
unintentional unrolling of the roll at least temporarily
during further fabrication processes. In the most
preferred form, food 14 is fabricated in a continual
35 process and has a constant consistency (aside from
moisture content) between the leading and trailing ends
136 and 138. In this regard, food 14 itself adheres to

1 support material 16 and specifically food 14 does not
include an additive or adhesive which secures food 14 to
support material 16.

The strips of food 14 and support material 16
5 including deposit 144 can be rolled in roll-up section 76
in the conventional manner so that support material 16 is
located on the outside of the roll, trailing edge 138 is
located on the periphery of the roll, and leading edge 136
is located adjacent the center of the roll and in the most
10 preferred form, with the strip of support material 16 and
food 14 being rolled around leading end 136 which is cut
and into a roll having multiple rotations. According to
the teachings of the present invention, deposit 144 will
cause food 14 adjacent to trailing end 138 to adhere to
15 support material 16 on the underlying wind of rolled food
item 110 and specifically without requiring the use of a
label. It should be appreciated that roll-up section 76
can include a pressure plate such as of the type disclosed
in U.S. Patent Nos. 5,205,106; 5,284,667; 5,455,053 and
20 5,723,163 to place pressure upon and to adhere food 14 of
increased tackiness within deposit 144 to support material
16 to thus secure the strip of food 14 and support
material 16 in a rolled or coiled condition during later
fabrication steps such as in wrapping and other packaging
25 operations.

The spray liquid should be applied by nozzles 142 in
deposits 144 in an amount so that food 14 develops
sufficient tackiness to be adherable to the strip of support
material 16. Specifically, the adhesion of food 14 on
30 support material 16 depends on the viscoelastic and the
surface tension properties of food 14. Support material 16
is silicone coated in the most preferred form to achieve
just enough cohesive bond between food 14 and support
material 16, such that the former remains attached to the
35 later during processing and storage. However, food 14 peels
easily off support material 16 for consumption. Studies
with adhesive strength of synthetic films showed that the

1 higher the wettability of the film, the greater the adhesive
strength between the product and the film. The normal water
activity of food 14 does not allow support material 16
(whose wettability has been reduced by silicone coating in
5 the preferred form) to adhere to trailing edge 138 of food
14 during the formation of rolled food item 110. According
to the teachings of the present invention, the water
activity of food 14 within deposit 144 at trailing edge 138
was increased by the application of the spray liquid just
10 before rolling in roll-up section 76. Because of the
viscoelastic nature of food 14, the pressure applied in
roll-up section 76 to trailing edge 138 of rolled food item
110 helps in the adhesion of deposit 144 of food 14 to the
body of the roll. It was observed that too much moisture in
15 food 14 also decreases the adhesion characteristics of food
14.

In this regard, a method was devised to measure the
adhesion strength of the formed rolled food item 110. A
texture analyzer, Model XT2, made by Stable Micro Systems,
20 England was used for this purpose. The sample holder
consisted of an aluminum rod hinged between two clamps,
which in turn were attached to a wooden base. The whole
assembly was attached to the texture analyzer in such a way
that the rod is positioned horizontally, crossways to the
25 operator, directly beneath the probe of the texture
analyzer. A sample rolled food item 110 was collected as
soon as rolled food item 110 was formed in roll-up section
76. A 1.2 cm by 1.2 cm VELCRO sticky back square was gently
taped to rolled food item 110 in such a way that trailing
30 edge 138 of support material 16 aligns with an edge of the
square. Rolled food item 110 was slipped into the aluminum
rod and was placed in contact with the probe of texture
analyzer already equipped with a complementary VELCRO sticky
back square. The rod was then secured between the clamps,
35 and the tensile strength required to peel trailing edge 138

1 of rolled food item 110 was recorded. The separation speed
of the probe was set at 2 mm/sec.

For proper adhesion of trailing edge 138 of the strip of
support material 16 and food 14 to the roll body, a minimum
5 adhesive strength of 42 grams-force/cm², measured through the
peel off test as described above, was required. An adhesive
strength of 100 to 300 grams-force/cm² was found to be
optimum. A water activity above 0.59 in deposit 144 gives
proper adhesion of rolled food item 110. However, a water
10 activity above 0.64 results in less tacky products. The
optimal range therefore, is 0.59-0.64 water activity for
food 14 after the application of the spray liquid.

It should be appreciated that after fabrication has
been completed, the spray liquid within deposit 144 over
15 time may decrease such as the result of evaporation or
dispersion throughout the remaining portions of food 14 to
be of an amount to reduce its tackiness, even to an amount
which is insufficient to adhere food 14 to the strip of
support material 16. However, the forces which would tend
20 to unintentionally unroll rolled food item 110 is
considerably less after fabrication. In fact after
fabrication, reduction of tackiness may desirably increase
the ease at which rolled food item 110 can be initially,
intentionally unrolled by the consumer. Additionally, the
25 evaporation and/or dispersion of the spray liquid from
deposit 144 is also advantageous in the reduction of the
possibility of the degradation of food 14 in deposit 144
as the result of the increased moisture content including
but not limited to molding. In this regard, it should be
30 appreciated that if nozzles 142 were operated continuously
or in a manner to spray substantial portions of the strip
of food 14 and support material 16 in an amount to develop
adhering tackiness, the shelf life of the resulting rolled
food item could be significantly reduced to an extent
35 which would make it unmarketable.

1 Rolled food item 110 according to the teachings of the
present invention is advantageous over prior rolled food
items. In particular, the strip of food 14 and support
material 16 is contacted only by a spray and in particular
5 is not mechanically contacted such as required during the
application of labels. Further, in the most preferred
form, only water is added and particularly no other food
ingredient such as corn syrup is added which could affect
the consistency, taste or appearance of food 14.
10 Additionally, problems in the handling of corn syrup or
like food additives including clogging additive passages
and stickiness when contacting other surfaces and
apparatus components including the cleaning thereof is
avoided when water is utilized. In fact, existing
15 fabrication equipment can be easily modified by the simple
replacement of the labeler and associate label applying
accessories or other fabrication unrolling prevention
provisions with nozzles 142. In the preferred form with
only water being sprayed, clogging and cleaning
20 requirements of nozzles 142 are minimized in comparison to
the problems associated with moving and cleaning corn
syrup or similar food adhesives. Additionally, the
fabrication and inventory costs for labels as well as the
capital costs associated with the fabrication and
25 application of such labels are avoided. Thus, existing
fabrication equipment and its operating conditions can be
utilized without significant change and in many cases with
more trouble free operation.

Now that the basic teachings of the present invention
30 have been explained, many extensions and variations will
be obvious to one having ordinary skill in the art. For
example, although the operation of spray nozzles 142 is
shown while the strip of food 14 and support material 16
is being rolled adjacent to its leading end 136, deposit
35 144 can be provided at any position upstream of roll-up
section 76 including while the strip of food 14 and
support material 16 is generally in a planar condition

1 according to the teachings of the present invention.
Similarly, although the operation of spray nozzles 142
is shown while the strip of food 14 and support material
16 is of its marketable length, deposit 144 can be sprayed
5 on food 14 and support material 16 prior to cutting into
multiple strips and/or cutting to length according to the
teachings of the present invention when food 14 is
continuously applied to continuous roll stock of support
material 16.

10 Thus since the invention disclosed herein may be
embodied in other specific forms without departing from
the spirit or general characteristics thereof, some of
which forms have been indicated, the embodiments
described herein are to be considered in all respects
15 illustrative and not restrictive. The scope of the
invention is to be indicated by the appended claims,
rather than by the foregoing description, and all changes
which come within the meaning and range of equivalency of
the claims are intended to be embraced therein.

CLAIMS

1. Method for fabricating a rolled food item,
comprising the steps of: providing a strip of support
5 material and food, with the strip of support material
and food having a trailing edge and a leading edge, with
the food having a tackiness; rolling the strip of
support material and food into a roll having a periphery
and a center, with the support material located on the
10 outside of the roll, with the trailing edge located on
the periphery of the roll and with the leading edge
located adjacent the center of the roll; and spraying a
deposit of a source of moisture at least on the food
adjacent to the trailing edge prior to its rolling into
15 the roll, with the source of moisture increasing the
tackiness of the food sufficient to be adherable to the
support material in the roll to at least temporarily
prevent unintentional unrolling of the roll.
- 20 2. The method of claim 1 wherein the strip providing
step comprises the step of providing the strip of
support material and food having an elongated length
between the trailing and leading edges; and wherein the
spraying step comprises the step of spraying the deposit
25 of a length considerably shorter than the elongated
length of the strip of support material and food.
3. The method of claim 2 wherein the spraying step
comprises the step of spraying the deposit with the
30 length approximately 10% of the elongated length of the
strip of support material and food.
4. The method of claim 1, 2 or 3 wherein the spraying
step comprises the step of spraying the deposit with a
35 food grade water free of adhesive type additives.

5. The method of any preceding claim wherein the strip providing step comprises the steps of providing a strip of support material having side edges and providing food having side edges spaced inwardly from the side edges of the strip of support material.
6. The method of any preceding claim wherein the spraying step comprises the step of spraying the deposit having side edges spaced inwardly from the side edges of the food.
7. The method of any preceding claim wherein the step of providing food comprises the step of providing a strip of food with the leading and trailing edges of the strip of food being coextensive with the leading and trailing edges of the strip of support material.
8. The method of any preceding claim wherein the spraying step comprises the step of spraying the deposit having a trailing edge coextensive with the trailing edge of the strip of food.
9. The method of any preceding claim wherein the strip providing step comprises the step providing food in the form of a sweetened dehydrated fruit based material.
10. The method of any preceding claim wherein the strip providing step comprises the step of providing the strip of support material in the form of silicon parchment paper.
11. Apparatus for fabricating a rolled food item, comprising, in combination: means for providing a strip of support material and food, with the strip of support material and food having a trailing edge and a leading edge, with the food having a tackiness; means for rolling the strip of support material and food into a

roll having a periphery and a center, with the support material located on the outside of the roll, with the trailing edge located on the periphery of the roll and with the leading edge located adjacent the center of the roll; means for spraying a deposit of a source of moisture at least on the food adjacent to the trailing edge prior to its rolling into the roll, with the source of moisture increasing the tackiness of the food sufficient to be adherable to the support material in the roll to at least temporarily prevent unintentional unrolling of the roll.

12. The apparatus of claim 11 wherein the strip of support material and food has an elongated length between the trailing and leading edges; and wherein the deposit has a length considerably shorter than the elongated length of the strip of support material and food.

13. The apparatus of claim 11 or 12 wherein the strip of support material and food comprises the strip of support material having side edges and a strip of food having side edges spaced inwardly of the side edges of the strip of support material, with the leading and trailing edges of the strip of food being coextensive with the leading and trailing edges of the strip of support material, with the deposit having side edges spaced inwardly from the side edges of the strip of food and having a trailing edge coextensive with the trailing edge of the strip of food.

14. Rolled food item comprising, in combination: a strip of support material and food, with the strip of support material and food having a trailing edge and a leading edge, with the strip of support material and food being rolled in a roll having a periphery and a center, with the support material located on the outside of the roll,

with the trailing edge located on the periphery of the roll, with the leading edge located adjacent the center of the roll, with the food having a first portion adjacent the trailing edge and a second portion of a substantially longer length than the first portion, with the first portion of the food having a moisture content greater than the moisture content of the second portion and so that the tackiness of the food is sufficient to adhere to the support material in the roll to at least temporarily prevent unintentional unrolling of the roll.

15. The rolled food item of claim 14 wherein the first portion has a length approximately 10% of the length of the strip of support material and food between the trailing and leading edges.

16. The rolled food item of claim 14 or 15 wherein the food has side edges spaced inwardly from the side edges of the strip of support material and with the first portion having side edges spaced inwardly from the side edges of the food.

17. The rolled food item of claim 14, 15 or 16 wherein the food comprises a strip of food having leading and trailing edges coextensive with the leading and trailing edges of the strip of the support material, with the first portion having a trailing edge coextensive with the trailing edge of the strip of food.

18. The rolled food item of any of claims 14 to 17 wherein the food is in the form of a sweetened dehydrated fruit based material.

19. The rolled food item of any of claims 14 to 18 wherein the support material is in the form of silicon parchment paper.

20. The rolled food item of any of claims 14 to 19 wherein the strip of food has the same consistency between the trailing and leading edges aside from increased moisture content in the first portion.

5

21. A method of fabricating a rolled food item substantially as hereinbefore described with reference to the accompanying drawings.

10

22. Apparatus for fabricating a rolled food item substantially as hereinbefore described with reference to Figures 3a and 3b of the accompanying drawings.

15

23. A rolled food item substantially as hereinbefore described with reference to the accompanying drawings.

75399.613



Application No: GB 0109973.8
Claims searched: 1-23

21

Examiner: Peter Trickey
Date of search: 1 November 2001

Patents Act 1977 Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.S): A2B (BMB11, BMB19, BMB21, BMC2, BMC7, BMC12, BMC17, BMP1, BMP5)
Int Cl (Ed.7): A21C 9/06; A21D 13/00, 13/08; A23G 3/00, 3/02; A23L 1/212; A23P 1/08
Other: Online: EPODOC, WPI, JAPIO

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	US 5853836 A (Zoss) See entire document, especially Figure 2 and column 3 lines 35-57	1, 9-11
X	US 5455053 A (Zimmermann) See entire document, especially column 2 line 53 to column 3 line 10	1, 9-11
X	US 3798343 A (Vitale) See entire document, especially Figures 2-3	1, 11
X	US 3704664 A (Fisher) See entire document	1, 11

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.